## A Simple Method for Reducing Cigarette Caused Upholstery Fires

One of the best kept secrets in the upholstery industry is that clean cellulosic fabrics do not ignite from cigarettes. It is generally thought that cigarette ignition resistance of cellulosic fabrics decreases with increasing fabric weight. However, even such heavy cotton fabrics as Haitian cotton will not ignite by cigarettes if rinsed in deionized or low hardness water.

Only cellulosic fabrics which contain certain compounds—primarily alkali metal ions such as potassium, sodium or calcium—support smoldering ignition. Such ions are found naturally in raw cotton (which is used in many upholstery fabrics) or as residues of dye assistants, softeners, detergents, etc.

The effect of many compounds on smoldering in general has been discussed (1-3). Others have shown in detail how increase in alkali metal ion concentration decreases cigarette ignition resistance of fabrics and the minimum concentration necessary to cause cigarette ignition and continued smoldering of fabric/foam combinations (4-6). Smolder promoters used to be added to cigarette tobacco to keep cigarettes burning while not puffed, but modern fertilization practices obviated the need for such additives. However, the smoldering rate and ash appearance of cigarette paper is modified by addition of, for example, sodium and potassium nitrate (7). Other tobacco smoldering promoters and inhibitors have been studied experimentally (8).

A simple test could be carried out by furniture and fabric manufacturers: a sample of a cellulosic upholstery fabric is rinsed in deionized or soft water, allowed to dry thoroughly and used in a fabric/foam mockup. A similar mockup is made from unrinsed fabric, and their reaction to ignited cigarettes observed. If there is considerably less smoldering of the rinsed mockup, a modification of the finishing process would be indicated.

There appear to be several thus far overlooked opportunities:

• For upholstered furniture manufacturers: to have a much wider selection of cigarette ignition resistant fabrics—e.g., UFAC Class 1 as compared to Class 2—with little or no added cost.

cigarette ignition resistance which may be a merchandising advantage as well as reducing cigarette caused fire death incidents.

- For finishing manufacturers: to offer new products—e.g., dye assistants, softeners, etc.—which promote smoldering less so they would not have to be completely rinsed out. Others could contain smolder inhibitors (to be used, perhaps, in the backcoating of raw cotton fabrics) which are not wet finished and for which rinsing and drying would be a costly production step. Boric acid/borax smolder inhibitors are widely used, of course, in cotton batting for both cigarette and flame ignition resistance, and others are available (1-3).
- For suppliers of upholstery cleaning materials: to offer products with reduced tendency to smolder, and to counteract rinses.

John F. Krasny 4419 Westbrook Lane Kensington, Md. 20895

## References

- (1) Shafidazeh, F. et al., Role of Inorganic Additives in the Smoldering Combustion of Cotton Cellulose, Industrial and Engineering Chemistry, Product Research and Development, Vol. 21, 1982, p72.
- (2) McCarter, R. J., Smoldering Combustion of Cotton and Rayon, *Journal of Consumer Flammability*, Vol. 4, 1977, p346.
- (3) McCarter, R. J., Smoldering Combustion of Wood Fibers: Cause and Prevention, Journal of Fire and Flammability, Vol. 9, 1978, p116.
- (4) Ihrig, A. M. et al., Factors Involved in the Ignition of Upholstery Fabrics by Cigarettes, *Journal of Fire Sciences*, Vol. 4, 1986, p237.
- (5) Wu, E-Chung and A. M. Ihrig, The Effects of Oxygen and Potassium Ions on the Ignition of Upholstery Materials by a Smoldering Cigarette, 1991 Fire Safety Conference, Polyplastex International Inc., Pinellas Park, Fla.
- (6) Honeycutt, R. H., M. Pham and K. C. Adiga, Effect of Air Flow on Cigarette Ignition Propensity (in preparation).
  - (7) Owens, W. F. Jr., Effect of Cigarette Paper on

HAVE an opinion you want to share? A comment to offer? A suggestion to make? TCC will publish it for you provided it is timely and brief. Communications must be signed, and cannot be of a derogatory nature. The magazine reserves the right to edit all communications accepted for publication. Letters should be sent to: The Editors, Textile Chemist and Colorist. P. O. Box 12215. Research Triangle Park, N. C. 27709

Smoke Yield and Composition, 32nd Tobacco Chemist's Conference, Montreal, 1978.

(8) Yamamoto. T. and H. Tomita, Effect of Organic and Inorganic Salts on the Static Burn Rate of Cellulose Model Cigarettes, Japanese Tobacco and Salt Public Corp.. Central Research Institute Scientific Papers, Vol. 120, 1978, p93.